

## I

(Acts whose publication is obligatory)

**COUNCIL REGULATION (EC) No 989/2005****of 27 June 2005****amending Regulation (EC) No 1255/96 temporarily suspending the autonomous common customs tariff duties on certain industrial, agricultural and fishery products**

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty establishing the European Community, and in particular Article 26 thereof,

Having regard to the proposal from the Commission,

Whereas:

- (1) It is in the interest of the Community to suspend partially or totally the autonomous common customs tariff duties for a number of new products not listed in the Annex to Regulation (EC) No 1255/96 <sup>(1)</sup>.
- (2) A number of products which are referred to in the said Regulation should be withdrawn from the list in the Annex because it is no longer in the Community's interest to maintain suspension of autonomous common customs tariff duties or because the description needs to be altered in order to take account of technical product developments and economic trends on the market.
- (3) Accordingly, products whose description needs to be altered should be regarded as new products.
- (4) It is therefore appropriate to amend Regulation (EC) No 1255/96 accordingly.

(5) In view of the economic importance of this Regulation, it is necessary to rely upon the grounds of urgency provided for in point I.3 of the Protocol annexed to the Treaty on European Union and to the Treaties establishing the European Communities on the role of national parliaments in the European Union.

(6) Since this Regulation is to apply from 1 July 2005, it should enter into force immediately,

HAS ADOPTED THIS REGULATION:

*Article 1*

The Annex to Regulation (EC) No 1255/96 is hereby amended as follows:

1. The products set out in Annex I to this Regulation shall be inserted.
2. The products for which the codes are set out in Annex II to this Regulation shall be deleted.

*Article 2*

This Regulation shall enter into force on the day of its publication in the *Official Journal of the European Union*.

It shall apply with effect from 1 July 2005.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Luxembourg, 27 June 2005.

*For the Council*  
*The President*  
L. LUX

<sup>(1)</sup> OJ L 158, 29.6.1996, p. 1. Regulation as last amended by Regulation (EC) No 2271/2004 (OJ L 396, 31.12.2004, p. 13).

## ANNEX I

CN code	TARIC	Description	Rate of autonomous duty (%)'
ex 2903 43 00	10	1,1,1-Trichlorotrifluoroethane	0
ex 2903 49 10	10	Chloro-1,1,1-trifluoroethane	0
ex 2904 20 00	50	2,2'-dinitro-bibenzyl	0
ex 2906 29 00	20	1-Hydroxymethyl-4-methyl-2,3,5,6-tetrafluorobenzene	0
ex 2907 29 00	85	Phloroglucinol whether or not hydrated	0
ex 2909 60 00	10	Bis( $\alpha,\alpha$ -dimethylbenzyl) peroxide	0
ex 2915 39 90	60	1-phenylethyl acetate	0
ex 2916 39 00	85	2,6-difluorobenzoic acid	0
ex 2920 90 10	40	Dimethyl carbonate	0
ex 2920 90 85	50	tri iso octyl phosphite	0
ex 2921 42 10	85	3,5-dichloroaniline	0
ex 2921 51 19	20	Toluene diamine (TDA), containing by weight 78 % or more but not more than 82 % of 4-methyl-m-phenylenediamine and 18 % or more but not more than 22 % of 2-methyl-m-phenylenediamine, and with a residual tar content of not more than 0,23 % by weight	0
ex 2924 19 00	50	Acrylamide	0
ex 2924 29 95	91	3-hydroxy-2'-methoxy-2-naphthanilide	0
ex 2924 29 95	92	3-hydroxy-2-naphthanilide	0
ex 2924 29 95	93	3-hydroxy-2'-methyl-2-naphthanilide	0
ex 2924 29 95	94	2'-ethoxy-3-hydroxy-2-naphthanilide	0
ex 2924 29 95	96	4'-chloro-3-hydroxy-2',5'-dimethoxy-2-naphthanilide	0
ex 2926 90 95	25	Aminoacetonitrile hydrochloride	0
ex 2926 90 95	35	2-Bromo-2(bromomethyl) pentanedinitrile	0
ex 2932 99 70	40	1,3:2,4-Bis-O-(3,4-dimethylbenzylidene)-D-glucitol	0
ex 2932 99 85	30	Carbofuran (ISO)	0
ex 2933 19 90	30	3-methyl-1-p. -tolyl-5-pyrazolone	0
ex 2933 39 99	40	2-chloropyridine	0
ex 2933 59 95	85	Adenine	0
ex 2933 99 90	88	2,6-dichloroquinoxaline	0
ex 2935 00 90	88	N-(2-(4-amino-N-ethyl-m-toluidino)ethyl)methanesulfonamide sesquisulfate monohydrate	0

CN code	TARIC	Description	Rate of autonomous duty (%)'
ex 3205 00 00	10	Aluminium lakes prepared from dyes for use in the manufacture of pigments for the pharmaceutical industry <sup>(1)</sup>	0
ex 3208 90 19	85	Mixture containing by weight: — 30-45 % Polyamide resin; — 2-10 % Diazonaphthoquinone; — 50-65 % $\gamma$ -Butyrolactone.	0
ex 3402 11 90	10	Surfactant mixture, of disodium salts of dodecyl (sulphophenoxy)benzenesulphonic acid and oxybis (dodecylbenzenesulphonic acid)	0
ex 3811 90 00	10	Dinonylnaphthylsulphonic acid salt, in the form of a solution in mineral oil, for use as an additive for distillate fuels and lubricating oils <sup>(1)</sup>	0
ex 3814 00 90	40	Azeotrope mixtures containing isomers of nonafluorobutyl methyl ether and/or nonafluorobutyl ethyl ether	0
ex 3815 90 90	88	Catalyst, consisting of titanium tetrachloride and magnesium chloride, containing by weight on an oil- and hexane-free basis: — 4 % or more but not more than 10 % of titanium and — 10 % or more but not more than 20 % magnesium	0
ex 3815 90 90	89	Rhodococcus rhodocrous J1 bacteria, containing enzymes, suspended in a polyacrylamide gel, for use as a catalyst in the production of acrylamide by the hydration of acrylonitrile <sup>(1)</sup>	0
ex 3824 90 99	54	2-Hydroxybenzonitrile, in the form of a solution in <i>N,N</i> -dimethylformamide, containing by weight 45 % or more but not more than 55 % of 2-hydroxybenzonitrile	0
ex 3824 90 99	70	Preparation, in an aqueous solution, of tetramethylammonium hydroxide and a surfactant containing: — 2,38 % (+/-0,01) by weight of tetramethylammonium hydroxide, and — a surfactant of 100 to 500 ppm.	0
ex 3824 90 99	80	Preparation containing by weight 81 % or more but not more than 89 % bis (3,4-epoxy-cyclohexylmethyl)-adipate	0
ex 3824 90 99	97	Preparation containing by weight either 10 % or more but not more than 20 % of lithiumfluorophosphate or 5 % or more but not more than 10 % of lithium perchlorate in mixtures of organic solvents	0
ex 3904 69 90	97	Copolymer of chlorotrifluoroethylene and vinylidene difluoride	0
ex 3906 90 90	55	Mixtures containing copolymers of methyl acrylate and ethylene and polyether-ester copolymers containing terephthalic acid, in the form of granules or pellets	0
ex 3906 90 90	85	Non aqueous dispersion type polymers of esters of acrylic acid with a hydrolyzable silyl group at one or both polymer ends	0
ex 3908 90 00	40	Thermoplastic polyamide resin having a fire point of more than 750 °C, for use in the manufacture of deflection yokes of cathode ray tubes <sup>(1)</sup>	0

CN code	TARIC	Description	Rate of autonomous duty (%)'
ex 3911 90 99	75	Microspheres of a copolymer of divinylbenzene and styrene, of an average diameter of 220 µm or more but not exceeding 575 µm	0
ex 3926 90 99	75		
ex 3913 90 00	98	Sodium hyaluronate	0
ex 3919 10 69	95	Reflecting laminated sheet showing a regular pattern, consisting of a film of poly(methylmethacrylate), followed by a layer of acrylic polymer containing microprisms, a film of poly(methylmethacrylate), an adhesive layer and a release sheet	0
ex 3919 90 69	98		
ex 3919 90 31	70	Poly(ethylene terephthalate) sheet, covered on one side with an anti-static layer and a hardcoat layer and on the other side with an adhesive layer and a release sheet, in rolls, for the manufacture of optical filters <sup>(1)</sup>	0
ex 3920 20 21	30	Biaxially oriented polypropylene film with a coextruded layer of polyethylene on one side and a total thickness of 11,5 µm or more but not more than 13,5 µm.	0
ex 3920 91 00	93	Film of poly(ethylene terephthalate), whether or not metallised on one or both sides, or laminated film of poly(ethylene terephthalate) films, metallised on the external sides only, and having the following characteristics: <ul style="list-style-type: none"> <li>— a visible light transmission of 50 % or more,</li> <li>— coated on one or both sides with a layer of poly(vinyl butyral) but not coated with an adhesive or any other material except poly(vinyl butyral),</li> <li>— a total thickness not exceeding 0,2 mm without taking the presence of poly(vinyl butyral) into account,</li> </ul> for use in the manufacture of heat-reflecting or decorative laminated glass <sup>(1)</sup>	0
ex 3920 99 59	60	Film of a vinyl alcohol copolymer, soluble in cold water, of a thickness of 34 µm or more but not exceeding 90 µm, a tensile strength at break of 20 MPa or more but not exceeding 45 MPa and an elongation at break of 250 % or more but not exceeding 900 %	0
ex 3921 90 60	94	Composite sheet containing an acrylic coating and laminated to a high-density polyethylene layer, of a total thickness of 0,8 mm or more but not exceeding 1,2 mm	0
ex 3926 90 99	15	Glass fibre reinforced plastic traverse leaf spring for use in the manufacture of motor vehicle suspension systems <sup>(1)</sup>	0
ex 3926 90 99	25	Unexpansible microspheres of a copolymer of acrylonitrile, methacrylonitrile and isobornyl methacrylate, of a diameter of 3 µm or more but not exceeding 4,6 µm	0
ex 6909 19 00	60	Supports for catalysts, consisting of porous ceramic pieces, of a blend of silicon carbide and silicon, with a hardness of less than 9 on the Mohs scale, with a total volume not exceeding 65 liters, having per cm <sup>2</sup> of the surface of the cross section one or more closed channels at the tail end	0

CN code	TARIC	Description	Rate of autonomous duty (%)'
ex 7007 19 20	10	Glass plate of a diagonal size of 81,28 cm (+/- 1,5 cm) or more, but not exceeding 185,42 cm (+/- 1,5 cm), consisting of tempered glass; provided either with a mesh film and a near-infrared absorbing film or a sputtered conductive layer, with optional additional anti-reflex layer on one or two sides, for use in the manufacture of PDP video monitors or television sets <sup>(1)</sup>	0
ex 7007 29 00	10	Glass plate of a diagonal size of 81,28 cm (+/- 1,5cm) or more, but not exceeding 185,42 cm (+/- 1,5 cm), consisting of 2 sandwich plates laminated together; provided either with a mesh film and a near-infrared absorbing film or a sputtered conductive layer, with optional additional anti-reflex layer on one or two sides, for use in the manufacture of PDP video monitors or television sets <sup>(1)</sup>	0
ex 8501 10 99	81	DC stepping motor, with an angle of step of 18° or more, a holding torque of 0,5 mNm or more, a coupling bracket the exterior dimensions of which do not exceed 22 × 68 mm, a two phase winding and an output not exceeding 5 W	0
ex 8501 10 99	82	DC motor, brushless, with an external diameter not exceeding 29 mm, a rated speed of 1 500 (± 15 %) or 6 800 (± 15 %) rpm, a supply voltage of 2 or 8 V	0
ex 8501 10 99	83	Multiphase electric motor with D.C. current, without brush, of a normal power drive of 31 W (+/- 5 W) calculated with 600 rpm (revolution per minute), equipped with electronic circuit provided with sensors using Hall effect (electric power steering motor)	0
ex 8505 11 00	33	Neodymium-magnet discs with a diameter not exceeding 90 mm, whether or not containing a hole in the centre	0
ex 8507 80 94	30	Electric lithium-ion accumulator, with: <ul style="list-style-type: none"> <li>— a length of 35 mm or more, but not more than 45 mm</li> <li>— a width of 35 mm or more, but not more than 53 mm</li> <li>— a thickness of 3,5 mm or more, but not more than 7 mm</li> <li>— a mass of 15,5 g or more, but not more than 35 g</li> <li>— a rated capacity of 600 mAh or more, but not more than 780 mAh</li> <li>— a nominal voltage of 3,7 V</li> </ul> for use in the manufacture of mobile phones <sup>(1)</sup>	0
ex 8516 90 00	33	Stainless steel soleplate with heating wire, for use in the manufacture of electric irons (1) <sup>(1)</sup>	0
ex 8516 90 00	35	Steam iron, not capable of independent operation, for use in the manufacture of steam ironing systems <sup>(1)</sup>	0
ex 8522 90 98	44	Assembly for optical discs, comprising at least an optical unit and DC motors, capable or not of double layer recording	0
ex 8522 90 98	49	Magnetic head for playback of audio tapes, for use in the manufacture of products falling within heading 8 519 <sup>(1)</sup>	0

CN code	TARIC	Description	Rate of autonomous duty (%)'
ex 8529 90 81	44	LCD modules, solely consisting of one or more TFT glass or plastic cells, not combined with touch screen facilities, with or without backlight unit, with or without inverters and one or more printed circuit boards with control electronics for pixel addressing only	0
ex 8537 10 99 ex 8543 89 95	94 66	Unit consisting of two junction field effect transistors contained in a dual lead frame housing	0
ex 8537 10 99 ex 8543 89 95	95 65	Unit consisting of two metal oxide semiconductor field effect transistors contained in a dual lead frame housing	0
ex 8540 91 00	32	Electron gun of colour cathode-ray tubes with an anode voltage of 27,5 kV or more but not exceeding 36 kV	0
ex 8543 89 95	52	Opto-electronic circuit comprising one or more light-emitting diodes (LEDs), whether or not equipped with an integrated driving circuit, and one photodiode with amplifier circuit, whether or not with an integrated logic gate arrays circuit or one or more light-emitting diodes and at least 2 photodiodes with an amplifier circuit, whether or not with an integrated logic gate arrays circuit or other integrated circuits, contained in a housing	0
ex 8548 90 90	47	Unit consisting of two or more light emitting diode chips operating at a typical wavelength of 450 nm or more but not exceeding 660 nm, contained in a lead frame housing having a circular opening whose exterior dimensions without fittings – do not exceed 4 × 4 mm	0
ex 8548 90 90	48	Optical unit, consisting at least of a laserdiode and a photodiode operating at a typical wavelength of 635 nm or more but not exceeding 815 nm	0
ex 8548 90 90	49	LCD modules, solely consisting of one or more TFT glass or plastic cells, combined with touch screen facilities, with or without backlight unit, with or without inverters and one or more printed circuit boards with control electronics for pixel addressing only	0
ex 9405 40 35	10	Electric light assembly of synthetic material containing 3 fluorescent tubes (RBG) of a diameter of 3,0 mm (± 0,2 mm), of a length of 420 mm (± 1 mm) or more, but not exceeding 600 mm (± 1 mm), for the manufacture of goods of heading 8528 <sup>(1)</sup>	0

<sup>(1)</sup> Entry under this subheading is subject to conditions laid down in the relevant Community provisions (see Articles 291 to 300 of Commission Regulation (EEC) No 2454/93 of 2 July 1993 laying down provisions for the implementation of Council Regulation (EEC) No 2913/92 establishing the Community Customs Code (OJ L 253, 11.10.1993, p. 1)).

## ANNEX II

Code NC	TARIC
ex 2932 11 00	10
ex 2933 69 80	10
ex 3824 90 99	54
ex 3907 20 99	25
ex 3911 90 99	75
ex 3926 90 99	75
ex 3920 91 00	93
ex 3920 99 59	60
ex 3926 90 99	85
ex 8522 90 98	44
ex 8529 90 81	31
ex 8540 91 00	32
ex 8543 89 95	52
ex 8548 90 90	39
ex 8548 90 90	46